

제품 사양

치수	미터법	영국식
최대 고소작업 높이	44.44m	146ft
최대 플랫폼 높이	42.44m	139ft 3in
최대 조작 범위	25.60m	83ft 12in
최대 플랫폼 범위	25.00m	82ft
평판 운반 치수(L×W×H)	11.92m×2.44m×2.83m	39ft 1in×8ft×9ft 3in
표준 컨테이너 운송	모두 적용 가능	모두 적용 가능
전체 너비(차축 확장)	4.17m	13ft 8in
전체 너비(차축 수축 A)	2.44m	8ft
플랫폼 크기(길이×너비)	2.44m×0.91m	8ft×3ft
턴테이블 테일스윙(차축 확장)	1.39m	4ft 7in
턴테이블 테일스윙(차축 수축)	2.28m	7ft 6in
지상 간극	0.40m	1ft 4in
휠베이스(차축 확장)	4.07m	13ft 4in
휠베이스(차축 수축 B)	4.27m	14ft


성능		
안전한 작업 부하(무제한/제한)	300kg/454kg	661lb/1000lb
최대 작업자 수	3	3
등급성	45%	45%
이동 속도(견인)	≥6.0km/h	≥3.73mph
이동 속도(상승)	≥1.1km/h	≥0.68mph
최대 고소작업 경사	5°	5°
터릿 회전	360°연속	360°연속
플랫폼 회전	180°	180°
지브 무브먼트	230°	230°
메인 붐 최대 각도	75°	75°
회전 반경(차축 확장)	2.99m/5.41m	10ft/17ft 9in
회전 반경(차축 수축)	8.27m/10.85m	27ft 2in/35ft 7in
타이어	445/50-D710	445/50-D710

중량		
전체 중량	23000kg	50706lb


전원		
리튬 배터리	358.4V/173Ah	358.4V/173Ah
비상 전원 공급 장치	12V	12V
디젤 탱크	100L	26gal
펌프 모터	360VDC/30kW	360VDC/30kW
유압 탱크	230L	60gal



하이브리드



동작 범위



기능

표준 항목

- 적재물 감지 장치
- 12V DC 보조 전원
- 유압유 방열기
- 혹독 환경 키트
- 결합 진단 시스템
- 턴테이블 보호 잠금 장치
- 고강성 붐 장치
- 완전 개방식 새시 덮개
- 플랫폼 측 AC 전선 연결
- 하강 및 이동 경보
- 좌우 180° 스윙 플랫폼
- 플랫폼 회전 각도 모니터링
- 플랫폼 하단부 보호
- 비례 조이스틱 컨트롤
- 느슨하고 깨진 체인 모니터링
- 고속 및 저속 모니터링
- 작동 상태 모니터링
- 엔진 시동 및 정지 보호
- Rexroth 유압 구동 장치
- 자동 조향 각도 매칭
- 구동 강제 센트 및 합병 기능
- 음압 제동 장치(감지 장치 포함)
- 실시간 기계 상태 표시 장치
- 범주 3 안전 아키텍처 - ISO 13849-1
- 작업자 압출 방지 보호 장치
- 4.2m 진폭의 가요성 지브(각도 감지 기능 제공)
- 360° 턴테이블 연속 회전(검사 기능 제공)
- 확장 가능한 새시(독점 특허 디자인 보유)
- 경적
- 기울기 경보
- 시간계
- 드라이브 활성화
- 점멸 LED 비콘
- 4륜 구동
- 4륜 스티어링
- 인시츄 차축 확장 장치
- 자체 레벨 조정 플랫폼



관절 붐-BT



고소작업
높이-44m



지브



하이브리드-H



힘준한
지형-RT



새로운 윈키 인시츄레이션 액슬 확장
기술 글로벌 특허 보호



표준 컨테이너 운송

ZHEJIANG DINGLI MACHINERY CO., LTD.

Address: No.188 Qihang Road, Deqing, Zhejiang P.R.C 313219

Telephone: +86(572)8681688

E-Mail: export@cndingli.com

Https://www.cndingli.com

Due to 연속 technology updates, technical parameters are subject to change without notice. This picture book is for reference only, the actual product shall prevail. The copyright is owned by zhejiang dingli, any content may not be copied for any purpose without written permission.

2025-03

